

SNAP CODE: 030320

SOURCE ACTIVITY TITLE: PROCESSES WITH CONTACT
Fine Ceramics Materials

NOSE CODE: 104.11.11

NFR CODE: 1 A 2 f

1 ACTIVITIES INCLUDED

This chapter covers emissions released from combustion processes within the production of fine ceramics. However, in the following if useful for description, also non-combustion emissions are mentioned.

2 CONTRIBUTION TO TOTAL EMISSION

The contribution of fuel use related emissions released from the production of fine ceramics to total emissions in countries of the CORINAIR90 inventory is given as follows:

Table 1: Contribution to total emissions of the CORINAIR90 inventory (28 countries)

Source-activity	SNAP-code	Contribution to total emissions [%]							
		SO ₂	NO _x	NMVOG	CH ₄	CO	CO ₂	N ₂ O	NH ₃
Fine Ceramics Materials	030320	0.2	0.1	-	-	0.3	0.3	0.1	-

0 = emissions are reported, but the exact value is below the rounding limit (0.1 per cent)

- = no emissions are reported

3 GENERAL

3.1 Description of activities

The manufacture of ceramic clay involves the conditioning of the basic ores by several methods. These include the separation and concentration of the minerals by screening, floating, wet and dry grinding, and blending of the desired ore varieties. The basic raw materials in ceramic clay manufacture are kaolinite (Al₂O₃·2SiO₂·2H₂O) and montmorillonite [(Mg, Ca)O·Al₂O₃·5SiO₂·nH₂O] clays. Caoline or limestone are used as additives. The clays are refined by separation and bleaching, blended, kiln-dried, and formed into such items as whiteware, heavy clay products (brick, etc.), various stoneware, and other products such as diatomaceous earth, which is used as a filter aid. /4/

The oven temperature reaches about 1100 °C. Most commonly natural gas is burned to heat the ovens, but other fuels are possible. Electric heated ovens are used in small scale ovens. Usually a tunnel shaped oven is used, but other types are used as well.

3.2 Definitions

3.3 Techniques

It can be assumed, that similar techniques are in use as described in chapter B3319.

3.4 Emissions

Pollutants released are dust, sulphur oxides (SO_x), nitrogen oxides (NO_x), volatile organic compounds (non-methane VOC and methane (CH₄), carbon monoxide (CO), carbon dioxide (CO₂), nitrous oxide (N₂O), fluoride (F_g), Chlorine (Cl_g) and ammonia (NH₃). According to CORINAIR90 the main relevant pollutants are SO₂, NO_x, CO, and CO₂ (see also table 1).

In the Netherlands, emissions from fine ceramic materials production represent scarcely 5 % of the emissions from bricks and tiles production /2/. The high temperatures of the firing kilns are also conducive to the fixation of atmospheric nitrogen and the subsequent release of NO_x.

It can be assumed, that formation mechanisms and formation processes of pollutants are similar to those described in chapter B3319. /cf 4/

3.5 Controls

Emission reduction techniques are almost non-existent.

4 SIMPLER METHODOLOGY

The simpler methodology involves applying an appropriate emission factor to either production or energy consumption statistics.

5 DETAILED METHODOLOGY

If an extensive measuring programme is available, emissions can be calculated on for an individual plant.

6 ACTIVITY STATISTICS

Standard production and energy statistics available from national or international statistical publications.

7 POINT SOURCE CRITERIA

The production of fine ceramics is usually executed in rather small plants can be considered as area sources.

8 EMISSION FACTORS, QUALITY CODES AND REFERENCES

For the situation in the Netherlands, the following can be proposed:

Emission factors are given in kg per ton product:

SO ₂ :	0.2 - 2.7
F _g :	0.2 - 2.8
Cl _g :	0.1
CO ₂ :	300 - 1600
NO _x :	0.6 - 2.0
dust *:	0.35 - 0.80

* dust consists of clay particles, the composition may vary widely.

The following Table 2 contains fuel related emission factors for the production of fine ceramics based on CORINAIR90 data in [g/GJ]. Technique related emission factors, mostly given in other units (e.g. g/Mg product), are listed in footnotes. In the case of using production statistics the specific energy consumption (e.g. GJ/Mg product) has to be taken into account, which is process and country specific. Within CORINAIR90 a range for the specific energy consumption of 8.8 - 100 GJ/Mg product has been reported.

Table 2: Emission factors for the production of fine ceramics⁷⁾

			Emission factors							
	Type of fuel	NAPFUE	SO ₂ ³⁾	NO _x ⁴⁾	NMVOC	CH ₄	CO ⁵⁾	CO ₂ ⁶⁾	N ₂ O	NH ₃
		code	[g/GJ]	[g/GJ]	[g/GJ]	[g/GJ]	[g/GJ]	[kg/GJ]	[g/GJ]	[g/GJ]
s coal	hc steam	102	650 ¹⁾	160 ¹⁾	15 ¹⁾	15 ¹⁾	100 ¹⁾	93 ¹⁾	4 ¹⁾	
s coal	hc sub-bituminous	103	610 ¹⁾ , 609 ²⁾	40 ¹⁾ , 39 ²⁾	1.5	1.5 ¹⁾		99 ¹⁾²⁾	8 ¹⁾	
s coal	bc brown coal/lignite	105	600 ¹⁾	140 ¹⁾	15 ¹⁾	15 ¹⁾	100 ¹⁾	113 ¹⁾	3.5 ¹⁾	
s coal	bc briquettes	106	220 ¹⁾	140 ¹⁾	15 ¹⁾	15 ¹⁾	100 ¹⁾	98 ¹⁾	3.5 ¹⁾	
s coke	hc coke oven	107	145 ¹⁾ , 144 ²⁾	45 ¹⁾²⁾	2.5 ¹⁾	2.5 ¹⁾		105 ¹⁾²⁾		
s coke	bc coke oven	108	650 ¹⁾	220 ¹⁾	5 ¹⁾	15 ¹⁾	90 ¹⁾	86 ¹⁾	3 ¹⁾	
s biomass	wood	111		200 ¹⁾	50 ¹⁾	30 ¹⁾		83-92 ¹⁾	4-14 ¹⁾	
l oil	residual	203	143-1,494 ¹⁾	100-180 ¹⁾	3-4 ¹⁾	0.1-5 ¹⁾	10-15 ¹⁾	73-78 ¹⁾	2-14 ¹⁾	
l oil	gas	204	85-1,410 ¹⁾	70-100 ¹⁾	1.5-2.5 ¹⁾	1-2.5 ¹⁾	10-12 ¹⁾	73-74 ¹⁾	2-14 ¹⁾	
l kerosene		206	69 ¹⁾	80 ¹⁾	2 ¹⁾	1 ¹⁾	12 ¹⁾	71 ¹⁾	14 ¹⁾	
l gasoline	motor	208	45 ¹⁾	80 ¹⁾	2 ¹⁾	1 ¹⁾	12 ¹⁾	71 ¹⁾	14 ¹⁾	
g gas	natural	301	0.3-8 ¹⁾	44-330 ¹⁾	2.5-10 ¹⁾	0.4-4 ¹⁾	10-111 ¹⁾	53-69 ¹⁾	1-3.7 ¹⁾	
g gas	liquified petroleum gas	303	0.04-2 ¹⁾	20-100 ¹⁾	1-2 ¹⁾	1-4 ¹⁾	13 ¹⁾	60-65 ¹⁾	1-3 ¹⁾	
g gas	coke oven	304	0.04-12 ¹⁾	50-100 ¹⁾	2.5-4 ¹⁾	2.5-4 ¹⁾	10-13 ¹⁾	49-59 ¹⁾	1-1.5 ¹⁾	

¹⁾ CORINAIR90 data, area sources

²⁾ CORINAIR90 data, point sources

³⁾ SO_x: 9,611 g/Mm³ fuel Mineral products, process heaters, NAPFUE 301 /1/
 290 g/Mg product General, SO₂ 260 g/Mg, SO_x 30 g/Mg /2/
 210 g/Mg product Future Value /2/

4)	NO _x :	850	g/Mg product	/2/
5)	CO:	1,600	g/Mg product	EPA value for ceramic industry
		130	g/Mg product	/2/
6)	CO ₂ :	255	kg/Mg product	General /2/

7) It is assumed, that emission factors cited within the table are related to combustion sources in the production of fine ceramics. Footnotes may also include emission factors for other process emissions.

9 SPECIES PROFILES

A profile of the clay used might be useful. This information however is not usually available.

10 UNCERTAINTY ESTIMATES

The quality classification of the emission factors expressed per ton product is estimated to be D.

11 WEAKEST ASPECTS/PRIORITY AREAS FOR IMPROVEMENT IN CURRENT METHODOLOGY

The fuel specific emission factors provided in table 2 are related to point sources and area sources without specification. CORINAIR90 data can only be used in order to give a range of emission factors with respect to point and area sources. Further work should be invested to develop emission factors, which include technical or fuel dependent explanations concerning emission factor ranges.

12 SPATIAL DISAGGREGATION CRITERIA FOR AREA SOURCES

13 TEMPORAL DISAGGREGATION CRITERIA

The production of fine ceramics can be either a continuous or a discontinuous process.

14 ADDITIONAL COMMENTS

15 SUPPLEMENTARY DOCUMENTS

Emission inventory in The Netherlands, 1992. Emission to air and water.

Emission factors to be used for the building industry, TNO report 89/091(1989) (in Dutch).

Environmental Protection Agency, Compilation of Air Pollutant Emission Factors AP 42

16 VERIFICATION PROCESSES

Verification of the emissions can be done by comparing the results of the calculations with measurements at the individual plant.

17 REFERENCES

- /1/ EPA (ed.): AIRS Facility subsystem; EPA-Doc 450/4-90-003; Research Triangle Park; 1990
- /2/ Huizinga, K.; Verburgh, J. J.; Mathijssen, A. J. C. M.; Loos, B.: Fijnkeramische Industrie; RIVM-report 736301124; RIZA-report 92.003/24; 1992
- /3/ Bouscaren, M. R.: CORINAIR Inventory, Default Emission Factors Handbook; Second Edition; Commission of the European Communities; Paris; 1992
- /4/ EPA (ed.): AP 42, CD-Rom, 1995

18 BIBLIOGRAPHY

For a detailed bibliography the primary literature mentioned in AP 42 may be used.

19 RELEASE VERSION, DATE AND SOURCE

Version: 2.1

Date: November 1995

Source: J J M Berdowski, P F J van der Most, R Wessels Boer
TNO
The Netherlands

Supported by: Otto Rentz, Dagmar Oertel
University of Karlsruhe (TH)
Germany

20 POINT OF ENQUIRY

Any comments on this chapter or enquiries should be directed to:

Pieter van der Most

HIMH-MI-Netherlands
Inspectorate for the Environment
Dept for Monitoring and Information Management
PO Box 30945
2500 GX Den Haag
The Netherlands

Tel: +31 70 339 4606

Fax: +31 70 339 1988

Email: pieter.vandermost@minvrom.nl