

AirBase version 3 data products on EEA data service

A short technical description. David Simoens, EEA, March 2009

1. Introduction

AirBase is a public air quality database containing air quality monitoring information for more than 35 countries throughout Europe. The list of countries included in AirBase is available as Annex A. The complete list of available components is given as Annex B. AirBase version 3 data products are available through the EEA data service at: <http://dataservice.eea.europa.eu/dataservice/metadetails.asp?id=1079>

General AirBase meta-information and links to further information on legal background (Eol decision) and annual data collection process are available at the indicated URL. The objective of the present document is not to repeat information available elsewhere but to describe the most relevant technical details of AirBase data products in order to facilitate their usage.

In case of any questions related to AirBase data products, please contact: david.simoens@eea.europa.eu

2. What's new in AirBase version 3 data products?

Some changes in comparison with AirBase version 2 data products deserve to be mentioned:

- Availability of the latest air quality data from the Eol2008 delivery (2007 data).
- Availability of a "main" measurement configuration (identified by measurement_european_group_code). The measurement_european_group_code can correspond to many occurrences of measurement configurations. Raw data and statistics are recorded under measurement_european_group_code. This code allows for a continuous time series of raw data (and related statistics) even in case of minor changes in the measurement configuration (see section 3a).
- A new station classification element in version 3 is the station_ozone_classification, relevant only for specific stations that record ozone concentrations. Its distinct attributes are: rural, rural background, suburban, urban and unknown. Values are available for more than 85% of stations recording ozone.
- A minimum of 5 statistical values are now systematically calculated for each component regardless of the statistics_average_group data type (see section 3a). These statistics are: annual mean, maximum, 98 percentile, 95 percentile and 50 percentile.
- A new statistical value is available based on hourly ozone data: SOMO35 (c > 70 ug/m3, year,corrected).
- Raw data plots are now available for all time series based on daily and hourly data, see section 4.
- KMZ file for geographic visualisation of Airbase stations, see section 4.
- The XML documents, which contain all metadata and statistics have a new structure compared to AirBase version 2. The structure is now defined in airbase.xsd (previously: airbase.dtd, see also section 3b and Annex C).
- More than 95% of the station_european_code values (i.e. the unique identifier for stations) for France have been changed. A similar change was already made for Germany in AirBase version 2.
- In the following 7 cases, component codes have been shifted, compared to AirBase version 2

component_code (AirBase_version2)	component_code (AirBase_version3)	component_name (AirBase_version3)
5654	5655	Indeno_123cd_pyrene in PM10 (aerosol)
5762	5759	Benzo(j)fluoranthene in PM10 (aerosol)
5609	5610	Benzo(a)anthracene in PM10 (aerosol)
5616	5617	Benzo(b)fluoranthene in PM10 (aerosol)
5625	5626	Benzo(k)fluoranthene in PM10 (aerosol)
5763	5419	Dibenzo(ah)anthracene in PM10 (aerosol)
76	2076	acidity(pH) (precip)

3. European data set

a) Data available in CSV format

AirBase_v3_stations.csv

Table with meta-information on AirBase stations (6 738 records). Station identifier and primary key for this table is: `station_european_code`. The information covers, among others: `station_name`, `station_local_code`, `station_altitude`, `type_of_station`, `station_type_of_area` and station co-ordinates.

AirBase_v3_statistics.csv

Table with annual statistics calculated from AirBase data (1 728 494 records). Relevant fields with statistical information are: `statistic_name`; `statistic_value`; `statistics_percentage_valid` and `statistics_number_valid`.

The primary key for this table is the combination of `station_european_code`, `component_code`, `measurement_european_group_code`, `statistics_year`, `statistic_name`, `statistics_average_group`. The latter field describes the data type, on which the statistics are based. The majority of statistics (>95%) is based on hourly or daily data, or on daily maximum (dymax) values. A smaller number of statistics is available for the following `statistics_average_group`s: 2week, 3hour, 3month, 4week, month, var (i.e. variable), week and year.

A 1-to-many relationship between station and statistics tables can be established by using the station identifier: `station_european_code`.

A 1-to-many relationship between statistics and measurement_configuration tables can be established by using the fields `station_european_code`, `component_code` and `measurement_european_group_code`.

AirBase_v3_measurement_configurations.csv

Table with measurement configurations (32 170 records), describing the conditions under which a component is measured at the station. The information covers, among others: `measurement_technique_principle`, `measurement_equipment`, `measurement_start_date`, `measurement_automatic`, `sampling_time_unit`, `integration_time_unit`, `calibration_frequency` and `calibration_method`.

The primary key for this table is the combination of `station_european_code`, `component_code` and `measurement_european_code`.

Technical details of the CSV format

The above tables are available as UTF-8 encoded text files. Field delimiter is a tab character (U+0009), records end with carriage return + line feed characters (U+000D, U+000A). A header row with field names is always included. Numerical values use the dot as decimal separator. There is no qualifier for string values.

b) Data available in XML format

AirBase_v3_xmldata.zip:

This zip archive contains 1 XML file per country with meta-information on networks, stations and measurement configurations. The XML files also include all statistical values. A description of the document structure in AirBase XML files including a list of legal elements and attributes is available in form of a XML schema (XSD). The schema is included within the zip archive as `airbase.xsd`.

All tables mentioned in section 2a) have been directly generated from the XML files. Data extraction has been done by using XSLT (Extensible Stylesheet Language Transformations). The XSLT stylesheet that has been used for extracting statistical values (i.e. for generating `AirBase_v3_statistics.csv`) is given in Annex C. Another option for extracting data from the XML files is to use the Excel macros as available on [ETC/ACC website](#). More information on how to extract data from the XML files can be made available on demand.

AirBase_v3_stations.kmz:

This KMZ archive shows AirBase stations locations and characteristics as `station_european_code`, `station_local_code`, station name, `station_start_date`, `station_end_date`, `type_of_station`, `station_type_of_area`. Stations are categorized by country within separate folders. The KMZ file can be open in many earth browser applications as for example Google Earth.

4. Data by country (including raw data)

This section on EEA data service contains one zip archive per country with data in CSV and XML format, as explained in section 2. Country data files have been generated by splitting the European data sets into "slices" for individual countries. There is no other difference between country data and European data sets.

The country zip archives also include raw data files. These are organised in text files, each one representing 1 time series of data. All necessary meta-information about the time series is included in the file name, e.g.:

FR300160000700100day.1-1-1999.31-12-2007

Position 1 – 7 station_european_code (here: FR30016)
Position 8 – 12 component_code (here: 00007, i.e. Ozone)
Position 13 – 17 measurement_european_group_code (here: 00100)
Position 18 until first dot: data type (here: day)
followed by start date and end date of the time series

Data types in raw data file names correspond to the statistics_average_group values as used in the statistics tables, (see section 3a).

Raw data files are tab-delimited text files. The general format of hourly and daily raw data files is as follows:

Date Value1 Flag1 Value2 Flag2 Value3 Flag3 Value4 Flag4 ValueN FlagN

Hourly data (data type: hour and hour8)

The date in column 1 identifies the calendar day to which the record relates. Measurement values 1...24 and quality flags 1...24 in columns 2-49 correspond to the hours of that date. Value 1 is understood to represent the measurements during the first hour of the day (i.e.: 00:00-00:59), and so on.

Raw data files with data type hour8 contain running 8-hour means calculated from the corresponding hourly data. Their format is identical to hourly data, with 24 values and 24 flags per day. However, any hour8 value represents the mean of hourly values in the preceding 8-hour period. E.g. hour8 value 10 is based on hourly values 3...10 of the same day, the averaging period for hour8 value 1 starts on 17:00H of the preceding day.

Daily data (data type: day and dymax)

The date in column 1 identifies the calendar month to which the record relates. Measurement values 1...31 and quality flags 1...31 in columns 2-63 correspond to the days of that month. All records have 31 values and 31 flags. For months with less than 31 days, the records are filled with invalid data.

Raw data files with data type dymax contain daily maximum values, based on running 8-hour means (see above). Both hour8 and dymax data files are only available for ozone and CO.

Quality flags in raw data

Flag values indicate the quality of the preceding measurement value. A quality flag value > 0 indicates valid measurement data. A quality flag <= 0 indicates invalid or missing data.

Raw data plots

Time series plots of AirBase raw data measurements are available as a separate product in EEA's Maps and Graphs service. Each plot presents 1 time series of raw data for a time span of eleven years: from 1 Jan 1997 until 31 Dec 2007. Plots are available for daily, hourly and daily maxima measurements, these represent more than 95% of the total number of raw data files. Only valid measurements are shown.

Annex A: Country codes, names and share in AirBase statistic data

code	country_name	%data	#components
AT	Austria	8.6	31
BA	Bosnia and Herzegovina	0.1	8
BE	Belgium	3.7	20
BG	Bulgaria	0.9	21
CH	Switzerland	2.0	13
CY	Cyprus	0.0	13
CZ	Czech Republic	3.9	15
DE	Germany	22.4	34
DK	Denmark	0.8	24
EE	Estonia	0.3	13
ES	Spain	12.1	22
FI	Finland	1.0	11
FR	France	12.7	12
GB	United Kingdom	8.4	86
GR	Greece	0.9	11
HR	Croatia	0.0	8
HU	Hungary	0.5	10
IE	Ireland	0.4	18
IS	Iceland	0.1	15
IT	Italy	9.5	32
LI	Liechtenstein	0.0	4
LT	Lithuania	0.4	23
LU	Luxembourg	0.1	9
LV	Latvia	0.2	18
MK	Macedonia - FYR of	0.5	9
MT	Malta	0.1	17
NL	Netherlands	3.3	65
NO	Norway	0.5	12
PL	Poland	2.3	19
PT	Portugal	1.9	13
RO	Romania	0.6	20
RS	Serbia	0.1	9
SE	Sweden	0.5	13
SI	Slovenia	0.3	6
SK	Slovakia	0.9	14

N.B.

code country_iso_code as used in AirBase

%data relative share of country data in AirBase data, 0.0 means less than 0.05%

#components number of components available in AirBase data

AD and TR Andorra and Turkey are missing in the above table, as no measurement data are available. However, a small number of air quality stations is registered in AirBase for these two countries (Andorra: 2, Turkey: 3).

Annex B: AirBase component codes, names, units and relative share in AirBase statistic data

code	component_name	measurement_unit	FWD	%data	#country
1	Sulphur dioxide (air)	ug/m3	yes	18.8	34
3	Strong acidity (air)	ug SO2/m3	no	0.7	7
4	Total suspended particulates (aerosol)	ug/m3	yes	2.9	18
5	Particulate matter < 10 µm (aerosol)	ug/m3	yes	9.0	35
6	Black smoke (air)	ug/m3	yes	1.1	15
7	Ozone (air)	ug/m3	yes	21.2	35
8	Nitrogen dioxide (air)	ug/m3	yes	17.2	35
9	Nitrogen oxides (air)	ug NO2/m3	yes	3.9	28
10	Carbon monoxide (air)	mg/m3	yes	9.4	34
11	Hydrogen sulphide (air)	ug/m3	no	0.1	6
12	Lead (aerosol)	ug/m3	yes	0.6	21
13	Mercury (aerosol)	ng/m3	yes	0.0	4
14	Cadmium (aerosol)	ng/m3	yes	0.4	16
15	Nickel (aerosol)	ng/m3	yes	0.3	14
16	Chromium (aerosol)	ng/m3	no	0.0	2
17	Manganese (aerosol)	ng/m3	no	0.0	2
18	Arsenic (aerosol)	ng/m3	yes	0.2	14
19	Carbon disulphide (air)	ug/m3	no	0.0	1
20	Benzene (air)	ug/m3	yes	1.3	29
21	Toluene (air)	ug/m3	no	0.4	13
22	Styrene (air)	ug/m3	no	0.0	2
24	1.3 Butadiene (air)	ug/m3	no	0.1	1
25	Formaldehyde (air)	ug/m3	no	0.0	1
26	Trichloroethylene (air)	ug/m3	no	0.0	1
27	Tetrachloroethylene (air)	ug/m3	no	0.0	1
29	Benzo(a)pyrene (precip)	ng/l	no	0.0	2
30	Polyaromatic hydrocarbons (air+aerosol)	ng/m3	no	0.0	1
32	Total non-methane hydrocarbons (air)	ug C/m3	no	0.1	5
33	Total volatile organic compounds (air)	ug/m3	no	0.1	4
34	Peroxyacetyl nitrate (air)	ug/m3	no	0.0	1
35	Ammonia (air)	ug/m3	no	0.1	5
36	Wet nitrogen deposition (flux)	mg N/(m2*m	no	0.0	1
37	Wet sulphur deposition (flux)	mg S/(m2*m	no	0.0	2
38	Nitrogen monoxide (air)	ug/m3	no	8.2	27
39	Hydrogen chloride (air)	ug/m3	no	0.0	2
40	Hydrogen fluoride (air)	ug/m3	no	0.0	1
41	Methane (air)	ug/m3	no	0.1	4
45	Particulate ammonium (aerosol)	ug/m3	no	0.0	2
46	Particulate nitrate (aerosol)	ug/m3	no	0.0	2
47	Particulate sulphate (aerosol)	ug/m3	no	0.1	8
51	HC C2-C6(excl. AROM. & CHLH) (air+aerosol)	ug/m3	no	0.0	1
63	Zinc (aerosol)	ng/m3	no	0.0	2
65	Iron (aerosol)	ng/m3	no	0.0	1
67	Total nitrate (air+aerosol)	ug N/m3	no	0.0	2
68	Total ammonium (air+aerosol)	ug N/m3	no	0.0	2

N.B.

code component_code as used in AirBase

FWD = yes mandatory pollutant, component_FWD as used in AirBase

%data relative share of component in AirBase data, 0.0 means less than 0.05%

#countries number of countries reporting this component

The component names in this table include both, the actual pollutant name and the matrix in which the concentrations are measured.

Annex B: AirBase component codes, names, units and relative share in AirBase statistic data (cont'd)

code	component_name	measurement_unit	FWD	%data	#country
69	Radioactivity ()	NULL	no	0.0	1
73	Copper (aerosol)	ng/m3	no	0.0	1
316	i-Hexane (2-methylpentane) (air)	ug/m3	no	0.0	2
351	acenaphtene (air+aerosol)	ng/m3	no	0.0	1
380	Benzo(b+j+k)fluoranthenes (air+aerosol)	ng/m3	no	0.0	1
394	n-Butane (air)	ug/m3	no	0.1	2
412	conductivity (precip)	uS/cm	no	0.0	1
416	cyclohexane (air)	pptv	no	0.0	1
428	Ethane (air)	ug/m3	no	0.1	2
430	Ethene (Ethylene) (air)	ug/m3	no	0.1	2
431	Ethyl benzene (air)	ug/m3	no	0.1	8
432	Ethyne (Acetylene) (air)	ug/m3	no	0.1	2
435	fluorene (air+aerosol)	ng/m3	no	0.0	1
441	n-Heptane (air)	ug/m3	no	0.1	3
443	n-Hexane (air)	ug/m3	no	0.1	3
447	i-Butane (2-methylpropane) (air)	ug/m3	no	0.1	1
449	i-Octane (2,2,4-trimethylpentane) (air)	ug/m3	no	0.0	2
450	i-Pentane (2-methylbutane) (air)	ug/m3	no	0.1	2
451	Isoprene (2-methyl-1,3-butadiene) (air)	ug/m3	no	0.1	1
464	m,p-Xylene (air)	ug/m3	no	0.1	8
475	n-Octane (air)	ug/m3	no	0.0	3
482	o-Xylene (air)	ug/m3	no	0.1	9
486	n-Pentane (air)	ug/m3	no	0.1	3
503	Propane (air)	ug/m3	no	0.1	2
505	Propene (air)	ug/m3	no	0.1	2
520	sum_sulph_diox_sulphate (air+aerosol)	ug S/m3	no	0.0	1
606	anthracene (air+aerosol)	ng/m3	no	0.0	1
609	Benzo(a)anthracene (air+aerosol)	ng/m3	no	0.0	1
616	Benzo(b)fluoranthene (air+aerosol)	ng/m3	no	0.0	1
622	Benzo(ghi)perylene (air+aerosol)	ng/m3	no	0.0	1
625	Benzo(k)fluoranthene (air+aerosol)	ng/m3	no	0.0	1
629	calcium (aerosol)	ug/m3	no	0.0	1
630	calcium (precip)	mg/l	no	0.0	1
631	chloride (aerosol)	ug/m3	no	0.0	1
632	chloride (precip)	mg/l	no	0.0	1
643	fluoranthene (air+aerosol)	ng/m3	no	0.0	1
648	acidity(H+) (precip)	ue H/l	no	0.0	1
654	indeno_123cd_pyrene (air+aerosol)	ng/m3	no	0.0	1
658	potassium (precip)	mg/l	no	0.0	1
660	magnesium (precip)	mg/l	no	0.0	1
664	ammonium (precip)	mg N/l	no	0.0	1
666	nitrate (precip)	mg N/l	no	0.0	1
669	sodium (precip)	mg/l	no	0.0	1
673	PCB_114 (air+aerosol)	pg/m3	no	0.0	1
674	PCB_118 (air+aerosol)	pg/m3	no	0.0	1
677	PCB_138 (air+aerosol)	pg/m3	no	0.0	1
679	PCB_141 (air+aerosol)	pg/m3	no	0.0	1
680	PCB_153 (air+aerosol)	pg/m3	no	0.0	1
683	PCB_157 (air+aerosol)	pg/m3	no	0.0	1
684	PCB_167 (air+aerosol)	pg/m3	no	0.0	1
685	PCB_170 (air+aerosol)	pg/m3	no	0.0	1
686	PCB_180 (air+aerosol)	pg/m3	no	0.0	1
689	PCB_183 (air+aerosol)	pg/m3	no	0.0	1

Annex B: AirBase component codes, names, units and relative share in AirBase statistic data (cont'd)

code	component_name	measurement_unit	FWD	%data	#country
690	PCB_187 (air+aerosol)	pg/m3	no	0.0	1
691	PCB_189 (air+aerosol)	pg/m3	no	0.0	1
692	PCB_194 (air+aerosol)	pg/m3	no	0.0	1
695	PCB_28 (air+aerosol)	pg/m3	no	0.0	1
701	PCB_52 (air+aerosol)	pg/m3	no	0.0	1
706	PCB_74 (air+aerosol)	pg/m3	no	0.0	1
707	PCB_99 (air+aerosol)	pg/m3	no	0.0	1
709	PCB_123 (air+aerosol)	pg/m3	no	0.0	1
712	phenanthrene (air+aerosol)	ng/m3	no	0.0	1
715	pyrene (air+aerosol)	ng/m3	no	0.0	1
719	sulphate (precip)	mg S/l	no	0.0	1
753	precipitation_amount (precip)	mm	no	0.0	1
754	precipitation_amount_off (precip)	mm	no	0.0	1
1045	Ammonium in PM2.5 (aerosol)	ug/m3	no	0.0	1
1047	sulphate in PM2.5 (aerosol)	ug/m3	no	0.0	1
1629	calcium in PM2.5 (aerosol)	ug/m3	no	0.0	1
1631	chloride in PM2.5 (aerosol)	ug/m3	no	0.0	1
2012	Lead (precip)	ug/l	no	0.0	1
2014	Cadmium (precip)	ug/l	no	0.0	1
2063	Zinc (precip)	ug/l	no	0.0	1
2065	Iron (precip)	ug/l	no	0.0	1
2073	Copper (precip)	ug/l	no	0.0	1
2076	acidity(pH) (precip)	pH units	no	0.0	3
4013	Mercury (air+aerosol)	ng/m3	no	0.0	3
4330	PCB_105 (air+aerosol)	pg/m3	no	0.0	1
4336	PCB_149 (air+aerosol)	pg/m3	no	0.0	1
4339	PCB_156 (air+aerosol)	pg/m3	no	0.0	1
4341	PCB_18 (air+aerosol)	pg/m3	no	0.0	1
4347	PCB_31 (air+aerosol)	pg/m3	no	0.0	1
4406	chrysene (air+aerosol)	ng/m3	no	0.0	1
5012	Lead in PM10 (aerosol)	ug/m3	no	0.1	3
5014	Cadmium in PM10 (aerosol)	ng/m3	no	0.1	4
5015	Nickel in PM10 (aerosol)	ng/m3	no	0.1	4
5018	Arsenic in PM10 (aerosol)	ng/m3	no	0.1	4
5029	Benzo(a)pyrene in PM10 (aerosol)	ng/m3	no	0.0	6
5129	Benzo(a)pyrene in PM10 (air + aerosol)	ng/m3	no	0.0	1
5380	Benzo(b,j,k)fluoranthene in PM10 (aerosol)	ng/m3	no	0.0	1
5419	Dibenzo(ah)anthracene in PM10 (aerosol)	ng/m3	no	0.0	3
5610	Benzo(a)anthracene in PM10 (aerosol)	ng/m3	no	0.0	4
5617	Benzo(b)fluoranthene in PM10 (aerosol)	ng/m3	no	0.0	2
5626	Benzo(k)fluoranthene in PM10 (aerosol)	ng/m3	no	0.0	4
5655	indeno_123cd_pyrene in PM10 (aerosol)	ng/m3	no	0.0	4
5759	Benzo(j)fluoranthene in PM10 (aerosol)	ng/m3	no	0.0	1
6001	Particulate matter < 2.5 µm (aerosol)	ug/m3	yes	0.5	28
6002	Particulate matter < 1 µm (aerosol)	ug/m3	no	0.0	2
6005	1-Butene (air)	ug/m3	no	0.1	2
6006	trans-2-Butene (air)	ug/m3	no	0.1	2
6007	cis-2-Butene (air)	ug/m3	no	0.1	2
6008	1-Pentene (air)	ug/m3	no	0.0	2

Annex B: AirBase component codes, names, units and relative share in Airbase statistic data (cont'd)

code	component_name	measurement_unit	FWD	%data	#country
6009	2-Pentenes (air)	ug/m3	no	0.1	2
6011	1,2,4-Trimethylbenzene (air)	ug/m3	no	0.0	4
6012	1,2,3-Trimethylbenzene (air)	ug/m3	no	0.0	3
6013	1,3,5-Trimethylbenzene (air)	ug/m3	no	0.0	4
6015	Benzo(a)pyrene (air+aerosol)	ng/m3	no	0.1	6

Annex C: XSLT Stylesheet for extracting annual statistics from XML files

```
<?xml version="1.0" encoding="UTF-8"?>
<xsl:stylesheet xmlns:xsl="http://www.w3.org/1999/XSL/Transform" version="1.0">
<!-- Stylesheet created by David Simoens EEA, March 2009 -->
<!-- Variable definition for tab delimited output -->
<xsl:variable name="newline" select="'&#x0A;'"/>
<xsl:variable name="tab" select="'&#x09;'"/>
<xsl:output method="text" encoding="UTF-8"/>

<xsl:template match="/">

  <!-- Write out field names -->
  <xsl:text>station_european_code</xsl:text>          <xsl:value-of select="$tab"/>
  <xsl:text>component_code</xsl:text>              <xsl:value-of select="$tab"/>
  <xsl:text>component_name</xsl:text>              <xsl:value-of select="$tab"/>
  <xsl:text>component_caption</xsl:text>          <xsl:value-of select="$tab"/>
  <xsl:text>measurement_unit</xsl:text>           <xsl:value-of select="$tab"/>
  <xsl:text>measurement_european_group_code</xsl:text> <xsl:value-of select="$tab"/>
  <xsl:text>statistics_period</xsl:text>          <xsl:value-of select="$tab"/>
  <xsl:text>statistics_year</xsl:text>            <xsl:value-of select="$tab"/>
  <xsl:text>statistics_average_group</xsl:text>    <xsl:value-of select="$tab"/>
  <xsl:text>statistics_shortcode</xsl:text>       <xsl:value-of select="$tab"/>
  <xsl:text>statistic_name</xsl:text>             <xsl:value-of select="$tab"/>
  <xsl:text>statistic_value</xsl:text>            <xsl:value-of select="$tab"/>
  <xsl:text>statistics_percentage_valid</xsl:text> <xsl:value-of select="$tab"/>
  <xsl:text>statistics_number_valid</xsl:text>     <xsl:value-of select="$tab"/>
  <xsl:text>statistics_calculated</xsl:text>       <xsl:value-of select="$newline"/>

  <xsl:apply-templates select="airbase/country/station/measurement_configuration"/>

</xsl:template>

<!-- Loop through the measurement configurations -->
<xsl:template match="measurement_configuration">

  <xsl:param name="station_european_code" select="../station_european_code"/>
  <xsl:param name="component_code" select="component_code"/>
  <xsl:param name="component_name" select="component_name"/>
  <xsl:param name="component_caption" select="component_caption"/>
  <xsl:param name="measurement_unit" select="measurement_unit"/>
  <xsl:param name="measurement_european_group_code" select="measurement_info/measurement_european_code"/>

  <!-- Loop through the statistic results -->
  <xsl:for-each select="statistics/statistics_average_group/statistic_set/statistic_result">

    <xsl:value-of select="$station_european_code"/>          <xsl:value-of select="$tab"/>
    <xsl:value-of select="$component_code"/>              <xsl:value-of select="$tab"/>
    <xsl:value-of select="$component_name"/>              <xsl:value-of select="$tab"/>
    <xsl:value-of select="$component_caption"/>          <xsl:value-of select="$tab"/>
    <xsl:value-of select="$measurement_unit"/>           <xsl:value-of select="$tab"/>
    <xsl:value-of select="$measurement_european_group_code"/> <xsl:value-of select="$tab"/>
    <xsl:value-of select="../../statistics_period"/>      <xsl:value-of select="$tab"/>
    <xsl:value-of select="../../@Year"/>                  <xsl:value-of select="$tab"/>
    <xsl:value-of select="../../@value"/>                 <xsl:value-of select="$tab"/>
    <xsl:value-of select="statistic_shortcode"/>         <xsl:value-of select="$tab"/>
    <xsl:value-of select="statistic_name"/>               <xsl:value-of select="$tab"/>
    <xsl:value-of select="statistic_value"/>              <xsl:value-of select="$tab"/>
    <xsl:value-of select="../statistics_percentage_valid"/> <xsl:value-of select="$tab"/>
    <xsl:value-of select="../statistics_number_valid"/>   <xsl:value-of select="$tab"/>
    <xsl:value-of select="../statistics_calculated"/>     <xsl:value-of select="$newline"/>
  </xsl:for-each>

</xsl:template>
</xsl:stylesheet>
```