**SNAP CODE:** 

#### 091003

109.07.04

6 D

OTHER WASTE TREATMENT Sludge Spreading

NOSE CODE:

**NFR CODE:** 

# **1** ACTIVITIES INCLUDED

Emissions from the spreading of sewage sludge can be considered as a part of a wastewater treatment plant.

# 2 CONTRIBUTION TO TOTAL EMISSIONS

#### Table 1: Contribution to total emissions of the CORINAIR90 inventory (28 countries)

Source-activity	SNAP-code*	Contribution to total emissions [%]							
		$SO_2$	NO <sub>x</sub>	NMVOC	$\mathrm{CH}_4$	CO	$CO_2$	$N_2O$	$\mathrm{NH}_3$
Sludge Spreading	091003	-	-	0.1	0.3	-	-	-	0.1

\* = SNAP90 code 090300

0 = emissions are reported, but the exact value is below the rounding limit (0.1 per cent)

- = no emissions are reported

# **3 GENERAL**

#### 3.1 Description

The sludge produced in a wastewater treatment plant is either burned, mechanically dried or dried by spreading in the open air. Information on emissions from the latter process is scarce. Emissions to air include odours. Recent measurements indicate that some ammonia is also produced. These emissions are considered in this chapter.

In the Netherlands some information on the composition of communal sludge is available. Some of the pollutants, especially halogenated hydrocarbons and PAHs might also become airborne on spreading.

# 4 SIMPLER METHODOLOGY

The simpler methodology would be to multiply the activity level by the ammonia emission factor to get the ammonia emission.

# 5 DETAILED METHODOLOGY

## 6 RELEVANT ACTIVITY STATISTICS

Standard statistics on sludge production and the fraction that is dried by spreading.

## 7 POINT SOURCE CRITERIA

This activity should be considered as an area source.

#### 8 EMISSION FACTORS, QUALITY CODES AND REFERENCES

The amount of ammonia produced by sludge spreading is determined by the dry matter content of the sludge and the total amount of ammoniacal nitrogen present. The dry matter content of a communal sludge may be between 4% (digested) and 5% (undigested).

Recent results from the United Kingdom gave a percentage ammonia of about 5% of the total ammonia-nitrogen content of the sludge.

## 9 SPECIES PROFILES

#### **10 UNCERTAINTY ESTIMATES**

# 11 WEAKEST ASPECTS/PRIORITY AREAS FOR IMPROVEMENT IN CURRENT METHODOLOGY

# 12 SPATIAL DISAGGREGATION CRITERIA FOR AREA SOURCES

## **13 TEMPORAL DISAGGREGATION CRITERIA**

Emissions from sludge spreading can be regarded as continuous.

# 14 ADDITIONAL COMMENTS

## **15 SUPPLEMENTARY DOCUMENTS**

NVA Slibcommissie 1994 Slibwijzer (in Dutch)

## **16 VERIFICATION PROCEDURES**

#### **17 REFERENCES**

Webb, J., ADA Food, Farming, Land and Leisure, personal communication, 1995.

Sommer, S.G., Olesen, J.E., Journal of environmental quality Vol. 20 (1991), pp. 679-683 Waste management. Effect of dry matter content and temperature on ammonia loss from surface applied cattle slurry.

## **18 BIBLIOGRAPHY**

## **19 RELEASE VERSION, DATE AND SOURCE**

Version :

Date : November 1995

1

Source : P.F.J. van der Most TNO The Netherlands

# 20 POINT OF ENQUIRY

Any comments on this chapter or enquiries should be directed to:

## Pieter van der Most

HIMH-MI-Netherlands Inspectorate for the Environment Dept for Monitoring and Information Management PO Box 30945 2500 GX Den Haag The Netherlands

Tel: +31 70 339 4606 Fax: +31 70 339 1988 Email: pieter.vandermost@minvrom.nl

Emission Inventory Guidebook